

Description

Packstat **PS021** is a finely creped, extremely stretchable and flexible paper masking tape for spray painting with subsequent oven-drying up to a temperature of 120°C.

Product Benefits

- The product is resistant to wet sanding and the very good adhesion of fillers or paints, (Water or solvent-based) to the reverse side of the tape prevents any kind of flaking.
- After the oven drying process with temperatures up to 120°C, it can be easily removed without tearing and without leaving any residue.

Applications

- Lacquering work.
- Can be used on painted metal, rubber, glass and chromed parts.
- Excellent flexibility for curves.

Technical Properties	Unit	Normal Value
Total Thickness	µm	170
Adhesion to Steel	N/cm	3.5
Elongation at Break	%	12
Tensile Strength	N/cm	47
Temperature Resistance	°C	120
Backing Material	-	Slightly-Creped Paper
Type of Adhesive	-	Natural Rubber
Hand Tradability	-	Very Good
Paint Anchorage	-	Very Good
Sharp Colour Edge	-	Good
Conformability	-	Good
Easy to Remove	-	Yes

Standard Sizes	Box Quantity	Markets
25mm x 50m	72	<ul style="list-style-type: none"> • Painting & Decorating • Art • Automotive
50mm x 50m	36	
75mm x 50m	24	
100mm x 50m	18	
Other sizes available on request		

22nd October 2018

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.