

### Description

Packstat **PS205** is a 40-micron, clear, acrylic transfer tape coated onto an 80-gsm yellow glassine paper release liner. This product is reverse wound to be used, recommended for all bonding, mounting and splicing applications.

### Product Benefits

- Service temperature: -30°C to +150°C.
- Reinforced with glass fibres for improved cohesive strength and clean break of adhesive.
- Long ageing performances.
- Excellent temperature resistance.
- Excellent resistance to UV.

### Applications

- Show card assembly.
- Point of sale assembly.
- Mounting albums, labels, leaflets, photos, posters, signs, stickers etc.
- Mounting sample cards.
- Mounting promotional items.
- Mounting display items.
- End tabbing of films, foils and papers.
- Core starting of films, foils and paper webs.

### Accreditations

Acid free / pH neutral - compliant to ISO 18902.  
Photographic activity test (PAT) for enclosure materials - compliant to ISO 18916

Technical Properties	Unit	Normal Value
Adhesion Film Thickness	Microns	40
Release Liner Thickness	Microns	67
Peel Adhesion on Stainless Steel	N/25mm	6.5
Colour	-	Clear
Core	mm	25.4

3<sup>rd</sup> December 2018

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.