

### **Description**

Packstat **PS270** is designed to adhere to a wide variety of substrates to form a protective barrier against scratches, bumps and general contamination of high value or sensitive materials in the aerospace industry such as aircraft seat shells. Apply at the start of a production line and dramatically reduce the number of defects and costly reworks due to surface damage. Can be left on for shipping purposes and removed cleanly when required.

Lower tack alternatives suitable for sensitive finishes are also available. Our **PS271**

Technical Properties	Unit	Normal Value
Reinforcement Polyethylene Film	Micron	50
Adhesive	-	Acrylic
Total Thickness	mm	2.06
Adhesion to Steel	N/25mm	4.5
Tensile Strength	N/25mm	<30
Elongation at Break	%	200

### **Recommendations:**

Surfaces must be clean, dry and free from grease or dirt. Recommended cleaning agent is Propan-2-ol (IPA). Product may be applied directly by hand using even and firm pressure. Shelf life will vary with temperature and humidity. Customers are advised to make their own assessment of our products under their own conditions for their own requirements.

6<sup>th</sup> December 2018

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.