

### Description

Packstat **PS022** is a finely crepe paper masking tape. The product is thin and flexible and therefore, suitable for all general masking applications, as well as oven drying applications up to a temperature off 100°C.

### Applications

- The product is resistant to wet sanding.
- Paints and fillers ad-here well to the backing.
- The material can be used on painted metal, rubber, glass and chrome parts.

Technical Properties	Unit	Normal Value
Total Thickness	µm	140
Adhesion to Steel	N/cm	3.4
Elongation at Break	%	10
Tensile Strength	N/cm	38
Temperature Resistance	°C	100
Backing Material	-	Slightly-Creped Paper
Type of Adhesive	-	Natural Rubber
Hand Tearability	-	Very Good
Paint Anchorage	-	Very Good
Sharp Colour Edge	-	Good
Conformability	-	Good
Easy to Remove	-	Yes

Standard Sizes	Box Quantity	Markets
12mm x 50m 25mm x 50m 38mm x 50m 50mm x 50m 100mm x 50m  <b>Other sizes available on request</b>	TBD	<ul style="list-style-type: none"> <li>• Painting &amp; Decorating</li> <li>• Art</li> <li>• Automotive</li> </ul>

12<sup>TH</sup> November 2018

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.