

Description

Packstat PS298 is a gloss polycloth laminate tape coated with an aggressive pressure sensitive adhesive.

Product Benefits

- Easy tear and unwind.
- Very high initial tack.
- Good abrasion resistance.
- Water resistant finish.
- Conformable to awkward shapes.
- Non-corrosive adhesive.

Main Applications

- Double glazing unit sealing.
- Designed as an all-purpose dust tape for general purpose applications.
- Used for sealing, bundling, short term masking and protecting.
- Excellent for jointing polyethylene sheeting in asbestos removal applications.
- Medium temperature duct sealing.
- Carpet joining and edging.

Accreditations

Conforms to European Directive 2000/53 EC (Lead, Chromium VI, Mercury, Cadmium free)

Technical Properties	Unit	Nominal Value
Thickness	mm	0.18
Breaking Load	N/cm	30
Elongation Adhesion Steel	% N/cm	15 3.7
Elongation Adhesion Self	% N/cm	15 2.3
Moisture Vapour Permeability	25g/m ² /24hrs	25g/m ² /24hrs
Service Temperature	°C	-50 to +65
Application Temperature	°C	+10 to +45
Storage Temperature	°C	+12 to +25
Colours	-	Silver, Black, White, Blue

24th October 2018

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.