

Description

Packstat **PS315** is a 135-micron strong and conformable polyethylene red or white film tape, coated with a high tack, removeable, acrylic adhesive. The product exhibits excellent adhesion to a range of substrates and is particularly designed for rough and embossed surfaces. It additionally has excellent UV resistance, allowing it to be used for a range of temporary masking and protection, external applications.

Product Benefits

- Conformable and flexible for use around irregular surfaces.
- Good initial tack for instant bonding and ultimate adhesion to a wide range of surfaces.
- Removes cleanly, without messy adhesive after use, for up to 6 months.
- Tack and robust film allowing good protection against mechanical damage.
- Performs well over a range of environmental conditions.
- Excellent UV performance for up to 6 months.
- Colour options allow good visibility for end user application.
- Can be applied manually or automatically, with no stretching of PE film.
- Service temperature -20 degrees C to +70 degrees C.
- Tearable by hand for ease of use.
- High humidity resistance.

Applications

- For the temporary masking and protection of a wide variety of different textured or rough substrates.
- Particularly suitable for masking textured powder coating profiles as well as aluminium and metal, window and door materials and other substrates.
- Protects the substrate for mechanical damage and stays in place until removed cleanly, without residue, for up to 6 months.

Technical Properties	Unit	Normal Value
Total Thickness	mm	0.135
Tensile Strength	N/cm	19
Adhesion to Steel	N/cm	2.6
Elongation at Break	%	400
Colours	-	Red, White

Issue Date: 18th January 2019

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Once issued however, it is an uncontrolled document. Please refer to our Terms & Conditions of Sale for further information.